

## BCSS-16

### 1080p AHD Stainless Steel IR Varifocal Bullet



#### Features:

- 1/3" Panasonic CMOS image sensor
- Full HD MP 1080p Resolution
- 2.8~12mm DC auto iris motorized megapixel lens
- Lens adjustable remotely using UTC
- 2pcs of IR LEDs
- True Day & Night with ICR mechanism
- 3D DNR / D-WDR (Digital Wide Dynamic Range)
- All in One (AHD, CVI, TVI, CVBS)
- Up to 1,640 ft HD-TVI transmission
- Stainless Steel Body (AISI 316 grade)
- Weatherproof / IP68 compliant
- 12VDC

#### Specifications:

<b>Image Sensor</b>	1/3" Progressive Panasonic CMOS image sensor
<b>Total Pixels / Active Pixels</b>	1956(H) x 1266(V) / 1944(H) x 1092(V)
<b>Day/Night</b>	Auto / Color / B&W / EXTERN
<b>Resolution</b>	HD-TVI: 1080p/30fps, 720P/60fps & ANALOG: 700TVL
<b>Min Illumination</b>	Color: 1.0 lux, BW : 0.5 lux, Color DSS: 0.002 lux, BW DSS: 0.0008 lux
<b>Video Output</b>	TVI / AHD / CVI / CVBS
<b>S/N Ratio</b>	More than 50dB (AGC off)
<b>AGC</b>	Off / 0-10
<b>Shutter Speed</b>	Auto / Manual (1/30 ~ 1/30,000 sec)
<b>Brightness</b>	0-20
<b>Backlight</b>	Off / BLC / HSBLC
<b>WDR/BLC</b>	Off / BLC / WDR
<b>D-WDR(ACE)</b>	Off / Low / Middle / High
<b>Defog</b>	Off / On
<b>White Balance</b>	AUTO / AUTOext / PRESET / Manual
<b>Image Mirror / Flip</b>	Off / On, Flip Off / On
<b>Privacy Mask</b>	21 Masks (BOX 15, POLYGON 7)
<b>Motion Detection</b>	Off / On
<b>Sharpness</b>	0 -10 steps
<b>3D DNR</b>	Off / Low / Middle / High
<b>Language</b>	English/Chinese/Japanese/Korean
<b>Power Supply / Consumption</b>	12VDC ± 10% / Max 4.5 Watt
<b>Operating Temp</b>	14°F ~ +122°F / -10°C ~ +50°C
<b>Humidity</b>	10% ~ 85%
<b>Lens</b>	2.8~12mm DC auto iris motorized MP lens (ICR)
<b>Dimensions</b>	6.6"(L) X 4.7"(H) X Ø2.8" / 168mm(L) X 120mm(H) X Ø72mm
<b>Weight</b>	3.4 lbs / 1520 (g)
<b>IP Rating</b>	IP68 compliant

All specifications are subject to change without notice.

© 2020 Broadsight Systems, Inc. All Rights Reserved. 07/20