

## BCM-S28

### 2 Megapixel IP STARVIS IR Corner Mount Camera



#### Features:

- 1/2.8" Sony 2MP STARVIS image sensor
- Max. 30fps/Full HD (1920x1080) Resolution
- ONVIF Ver17.06 Compliant
- Video compression (H.265, H.264, MJPEG)
- Triple streaming
- Real-WDR(Wide Dynamic Range)
- 2.8mm / F=1.6 Lens
- 30 pcs Covert IR LEDs
- 3D DNR (Digital Noise Reduction)
- Metal front panel for vandal resistant
- Audio (option)
- PoE (IEEE802.3af)

#### Specifications:

Image Sensor	1/2.8" Sony 2MP STARVIS image sensor
Scan System	Progressive Scan
Total Pixels	1945(H) x 1109(V)
Effective Pixels	945(H) x 1097(V)
Day/Night	Auto / Color / B&W / ICR Control
Resolution	1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 / 640x480 / 320x240
Video Output	CVBS 1.0Vp-p
True WDR	120dB
Video Compression	H.265/H.264/MJPEG
Max Frame Rate	Max 30fps@ 1920x1080
Video Quality	H.265 : Bitrate Control, H.264 : Bitrate Control, MJPEG : Quality Level Control
Video Streaming	Triple Stream ( RTP/RTSP , Unicast RTP , Multicast RTP )
Privacy Area	On / Off (16 Programmable Zones)
Motion Detection	432 Zone, Sensitivity 1 ~ 5 Step, On / Off
LAN Interface	10/100-base-T Ethernet auto sensing, PoE(IEEE 802.3af) Interface
DNR	2DNR, 3DNR
Protocol	TCP/IP,UDP/IP,RTP,RTSP,RTCP,NTP,HTTP,DHCP,FTP,SMTP,DNS,DDNS
Onvif	ONVIF Ver17.06
Power Supply	PoE, 12VDC ±10%
Operating Temp	32°F ~ +122°F / 0°C ~ +50°C
Humidity	10% ~ 90%
Lens	2.8~12mm / F=1.6 Lens
Dimensions	7.4"(W) X 5.5"(D) X 1.7"(H) / 190mm(W) X 140mm(D) X 43.2mm(H)
Weight	0.9 lbs / 390 (g)