

BPIR-C37

1080p CVI Covert
PIR IR Camera



Features:

- 1/2.8" Sony IMX322 CMOS image sensor
- 1080p CVI (4-in-1 (CVI/TVI/AHD/CVBS))
- 24 Covert IR LEDs (940nm)
- 3.7mm MP pinhole lens
- True Day & Night by ICR mechanism
- 3D-DNR (Digital Noise Reduction)
- SENS-UP
- UTC (Up The Coax)
- D-WDR (Digital Wide Dynamic Range)
- OSD remote (attached to cable)
- 12VDC

Specifications:

Image Sensor	1/2.8" SONY CMOS Sensor
Scan System	Progressive
Total Pixels / Effective Pixels	2000(H) x 1121(V) 2.24MP / 1936(H) x 1105(V) 2.12MP
Day/Night	Auto/Day Night/Ext
Resolution	1920x1080p(1080p/30fps), 1280x720p(720p/60fps) / Analog 700TVL (960H)
Min. Illumination	Color: 1.0 lux, BW: 0.5 lux, Color DSS: 0.002 lux, BW DSS: 0.001 lux
Video Output	CVI/TVI/AHD/CVBS
S/N Ratio	More than 50dB (AGC Off)
AGC, ACE, HLC, Freeze	Off/On
Shutter Speed	AUTO/MANUAL(1/30(25) ~ 1/60,000 sec)
SENS-UP	Off / X2 / X3 / X4
Brightness	0 -20 steps
WDR/BLC	Off/WDR/BLC
D-WDR	Off/0 ~ 8
Defog	Off/Auto
White Balance	Auto / One Push / Manual / Indoor / Outdoor
DNR	Off/Low/Middle/High
Mirror	Off/H/V/H&V
Sharpness	0 -10 steps
E. Zoom	X1 ~ X7
Gamma	0.45 / 0.50 / 0.55 / 0.60 / 0.65
Privacy Mask	32 Points
Motion Detection	Off/On (4 Points)
Language	English, Korean, Chinese
Power Supply	12VDC ± 10%
Operating Temp	14°F ~ +122°F / -10°C~ +50°C
Humidity	10% ~ 85%
Lens	3.7mm MP Pinhole Lens
Dimensions	2.4"(W) x 1.9"(D) x 3.5"(H)mm / 62(W) x 48(D) x 90(H)mm
Weight	0.2lbs/105g

All specifications are subject to change without notice.

© 2020 Broadsight Systems, Inc. All Rights Reserved. 12/20