

Specialty Cameras

1080p IP Covert Camera



This covert IP camera is available as a standalone camera or integrated into one of our specialty enclosures. The camera is attached to a 20-ft cable which connects to the network unit.

The high resolution imager and compact size make it ideal for discreet surveillance. A variety of mounting covers are included to enable a variety of mounting options.

Onboard analytics include motion detection, intrusion detection, people counting, loitering detection, tampering, and failure detection.

Power the unit with 12VDC and utilize Edge Recording to minimize cabling, or use PoE (802.3af) for power and video.

Features

- Full HD 1080p Resolution
- Onboard Analytics
- 3.7mm Pinhole Lens
- PoE or 12VDC
- Edge Recording up to 32GB
- ONVIF Profile S
- 20-ft Cable

Models:

| | |
|--------|--|
| BCM-10 | IP Camera, 1080p, 3.7mm Pinhole Lens, 20-ft Cable, PoE/12VDC |
|--------|--|

Specifications:

| | |
|----------------------|--|
| Sensor | 1/3" 1080p CMOS |
| Resolution | Max 1920 x 1080 |
| Scanning System | Progressive Scan |
| Minimum Illumination | Color: 1.0 lux BW: 0.007 lux DSS ON |
| Lens | 3.6mm, F2.5 (58° HFOV) |
| DSP Features | D/N, DWDR, DNR, DSS, BLC, AWB, Motion Detection |
| Compression Format | H.264 Baseline, Main, High Profile MJPEG |
| Streams | Dual stream (H.264, MJPEG) |
| Frame Rate | Max 30fps |
| Alarm | DI/DO 1 Channel |
| Network | 10 / 100 Base-T |
| Protocol | QoS Layer 3 DiffServ, TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTCP, RTP/UDP, RTP/TCP, mDNS, UPnP™, SMTP, DHCP, DNS, DynDNS, NTP, SNMPv1/v2c/v3 (MIBII), IGMP, ICMP, SSLv2/v3, TLSv1 |
| SD Card | microSD Slot (up to 32GB) |
| Power | 12VDC (6W), PoE 802.3af |
| Installation | Indoor |
| Operating Temp (°F) | 14° ~ 122° |
| Operating Temp (°C) | -10° ~ 50° |
| Construction | Camera Unit: Black Anodized Aluminum Network Unit: Plastic |
| Dimensions | Camera Unit: 1.1" Ø x 1.0" H (28mm Ø x 25 mm H) Network Unit: 4.2 x 1.0 x 4.9 (in) / 107 x 36 x 124 (mm) |