

BCS-150

Motorized Zoom Camera with 10X Optical Zoom



Features



- 1/3" Sony Ex-View HAD Double Scan CCD
- 700TVL Resolution, 0.01Lux
- 5-50mm 10X Optical Zoom
- True Day/Night
- DIS, 3D-DNR, Sense-Up, WDR
- OSD Menu

Model:

BCS-150	Day/Night Motorized Zoom Lens Camera, 700TVL, 5-50mm Optical Zoom, 12VDC
---------	--

Specifications:

Imager	1/3" Sony Ex-View HAD Double Scan CCD
Resolution	700TVL
Effective Pixels	976 H x 494 V
Scanning System	NTSC, 2:1 Interlaced
Video Output	1.0 Vp-p Composite, 75Ω
S/N Ratio	>54dB (AGC Off, DNR 128x)
Minimum Illumination	0.01Lux/F1.2 (Sense-Up Off), 0.00005Lux/F1.2 (Sense-Up x512)
Electronic Shutter	1/60 ~ 1/120,000 Second
White Balance	ATW, AWC, Push, Anti-CR, Manual (1800°K ~ 12,500°K)
Day Night	True Day Night w/ Mechanical IR Cut Filter: Auto, COL, B/W, Ext
DSP Features	DIS (Digital Image Stabilization), 2D/3D DNR (Digital Noise Reduction), Sense-Up (1,024x Max), WDR (Wide Dynamic Range, 150dB Max), ATR-Ex (Auto Tonecurve Reproduction), Mirror, Digital Pan/Tilt, Motion Detection, Zoom on Motion, Privacy Masking
Optical Zoom	10X Motorized Zoom Lens (5 – 50mm)
Digital Zoom	14X (Up to 140X Total Zoom)
Horizontal Viewing Angle	W: 64.2° T: 6.9°
Focus / Iris	Auto-Focus, Auto-Iris
Terminal Block	RS485, External Light Sensor, Alarm
RS485	Pelco D, 9600bps
Mounting Base	Attaches to Top or Bottom of Camera
Power Requirement	12VDC (8 ~ 28VDC), 240mA Max @ 12VDC
Operating Temp	-4 ~ +144°F (-20 ~ +60°C)
Construction	Aluminum Case
Humidity	< 80% RH
Dimensions	4.3" L x 2.5" W x 2.6" H (109mm L x 64mm W x 66mm H)
Weight	0.8 lbs (0.36 kg)



All specifications are subject to change without notice.

© Broadsight Systems, Inc. All Rights Reserved. 05/19