

BNH-5011 Series

Network Camera Housing



Shown: BNH-5011-PHB, BWM-5011 Wall Bracket

Models:

BNH-5011	Housing w/ Sunshield
BNH-5011-PB	Housing, PoE, Blower, w/ Sunshield
BNH-5011-PHB	Housing, PoE, Heater, Blower, w/ Sunshield
BWM-5011	Wall Mount for BNH-5011

Specifications:

Environment	Indoor / Outdoor
Housing Type	Side Opening
IP Rating	IP66
Sunshield	Included
Cable Entry	1 x Liquid-Tight Fitting 3-Cable Sealing Grommet
Cable Management	Sold Separately
Bracket	Part Number BWM-5011
Input Voltage	12VDC / PoE (802.3af) (-PB, -PHB versions) Terminal Block Provided in BNH-5011
Power Consumption	5W Heater, <2W Blower
Operating Temperature	Min -5°C ambient for >0°C Internal Max +50°C ambient
Construction	Aluminum with UV Protected Powder Coat Paint, Gray
Internal Dimen. (in)	2.75 x 2.95 x 6.9 (W x H x L)
Internal Dimen. (mm)	70x75x176 (W x H x L)

Features

- Power IP Camera (max 7W), Heater, and Blower Over a Single Network Cable Using Standard 15.4W PoE Port (802.3af).
- IP-Camera-Ready with Glass Viewing Window for Optical Clarity
- Installer-Friendly Side-Opening Design
- Sunshield Included, Heater and Blower Options
- Feed-Through Mount Accessory

The BNH-5011 Series camera housings offer an installer friendly design with side-opening access to the camera bay simplifying installation and camera servicing. The optional feed-through mount conceals power and video cables.

The housing's glass viewing window for optical clarity and PoE splitter for powering the housing with a single network cable make this housing an ideal enclosure for high-Megapixel IP cameras.

