

## AHD Pinhole Camera



### Features

- 2MP Resolution
- Quad Output CVBS / AHD / TVI / CVI
- 3.7mm Pinhole Lens
- Small Size for Covert Applications
- OSD Controller Built Into Cable

This compact AHD camera is available as standalone camera or integrated into one of our specialty enclosures. The camera output is selectable between multiple formats (CVBS / AHD / TVI / CVI) using the OSD control cable.

The high resolution imager and compact size make it ideal for discreet surveillance. The camera operates on 12VDC. A 2-axis mounting bracket is included.

### Models:

BCM-30	AHD Camera, 2MP, 3.7mm Pinhole Lens, OSD Cable, 12VDC
--------	---

### Specifications:

Sensor	1/3" CMOS
Effective Pixels	1944 (H) x 1092 (V) (2.1 MP)
Resolution	1080p @ 30 FPS, 720P @ 30FPS
Scanning System	Progressive Scan
Minimum Illumination	0.1 Lux@F2.5, 30IRE
Lens	3.7mm Pinhole, F2.5 (66° HFOV)
DSP Features	3D-DNR, Sens-up, D-WDR
Frame Rate	30fps
Power	12VDC, 130mA max
Installation	Indoor (<80% RH)
Operating Temp (°F)	14° ~ 122°
Operating Temp (°C)	-10° ~ 50°
Construction	Aluminum, Black Anodize
Dimensions	0.98" L x 1.02" W x 0.71" H 25mm L x 26mm W x 18mm H
Weight	0.04 LBS (17 g)

