

BB-29SS-HD

Stainless Steel Bulkhead HD Analog Camera



Features:

- Designed for “Peep Hole” and bulkhead applications
- 1/2.8” Sony STARVIS CMOS sensor
- Full HD Mega Pixel (1080P)
- 4 in 1 (AHD/TVI/CVI/CVBS)
- Auto Compensation & Long range transmission
- 2.9mm Waterproof Lens
- 3D DNR / (D-WDR)
- UTC (via coaxial cable)
- Stainless Steel Housing/AISI-316L
- Weatherproof / IP 67 Compliant
- DC12V
- NDAA Compliant

Specifications:

Image Sensor	1/2.8” Sony STARVIS CMOS sensor
Scan System	Progressive
Effective Pixels	1920(H) x 1080(V)
Day/Night	Auto/Color/B&W/EXTERN
Resolution	1080p@30fps/1080p@25fps
Min. Illumination	0.001 lux, (F=1.2)
Video Output	Universal AHD, CVI, TVI : 1080P, Analog: NTSC/ PAL CVBS
S/N Ratio	More than 50dB (AGC Off)
AGC	Off/0 - 15
Shutter Speed	AUTO/MANUAL(1/50(60) ~ 1/50,000 sec)
SENS-UP	Off/X2 – X30
Brightness	0 - 100
Backlight	Off/BLC/HSBLC
D-WDR	Off/0 ~ 8
Defog	Off/ Auto
White Balance	ATW/AWC/INDOOR/OUTDOOR/Manual/AWB
DNR	Off/Low/Middle/High
Mirror	Off/MIRROR/V-FLIP/ROTATE
Sharpness	0 - 10 steps
Privacy Mask	4 Masks
Motion Detection	Off/On
Language	English/Chinese/German/French/Italian/Spanish/Polish/Russian/Portuguese/Netherlands(Dutch)/Turkish/Korean/ Japanese
Power Supply / Consumption	12VDC ±10% / Max 1.5 Watt
Operating Temp	14°F ~ +122°F / -10°C ~ +50°C
Humidity	10% ~ 85%
Lens	2.9mm Waterproof Lens
Dimensions	1.4”(L) X 1.5”(Φ) / 35.6mm(L) X 28mm(Φ)
Weight	0.2 lbs / 110 (g)

All specifications are subject to change without notice.

© 2021 Broadsight Systems, Inc. All Rights Reserved. 01/21